



# MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Date of issue: 02/04/2013

Version 1.0

## SECTION 1. Identification

### Product identifier

Product number	818878
Product name	Lithium aluminium hydride (tablets) for synthesis
Synonyms	LAH

### Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Chemical for synthesis
-----------------	------------------------

### Details of the supplier of the safety data sheet

Company	EMD Millipore Corporation   290 Concord Road, Billerica, MA 01821, United States of America   SDS Phone Support: +1-978-715-1335   General Inquiries: +1-978-715-4321   Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5)  e-mail: mm_sds@merckgroup.com
---------	--

Emergency telephone	800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week
---------------------	--

## SECTION 2. Hazards identification

### GHS Classification

Substances which in contact with water emit flammable gases, Category 1, H260

Skin corrosion, Category 1A, H314

For the full text of the H-Statements mentioned in this Section, see Section 16.

### GHS-Labeling

#### Hazard pictograms



Signal Word  
Danger

#### Hazard Statements

H260 In contact with water releases flammable gases which may ignite spontaneously.

# MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

818878

Version 1.0

Product name

Lithium aluminium hydride (tablets) for synthesis

H314 Causes severe skin burns and eye damage.

## Precautionary Statements

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309 + P310 IF exposed or if you feel unwell: Immediately call a POISON CENTER or doctor/physician.

P402 + P404 Store in a dry place. Store in a closed container.

## OSHA Hazards

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

## Other hazards

None known.

## SECTION 3. Composition/information on ingredients

Formula	LiAlH <sub>4</sub>	H <sub>4</sub> AlLi (Hill)
CAS-No.	16853-85-3	
Synonyms	LAH	
Molar mass	37.95 g/mol	

## Hazardous ingredients

*Chemical Name ( Concentration)*

CAS-No.

*aluminium lithium hydride ( >= 90 % - <= 100 % )*

16853-85-3

## SECTION 4. First aid measures

### Description of first-aid measures

#### Inhalation

After inhalation: fresh air. Call in physician.

#### Skin contact

After skin contact: wash off with plenty of water. Immediately remove contaminated clothing. If available swab with polyethylene glycol 400. Call a physician immediately.

#### Eye contact

After eye contact: rinse out with plenty of water. Call a physician immediately.

#### Ingestion

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation!). Call a physician immediately. Do not attempt to neutralize.

Never give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed

Irritation and corrosion, Cough, Shortness of breath

Risk of corneal clouding.

## MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

818878

Version 1.0

Product name

Lithium aluminium hydride (tablets) for synthesis

---

The following applies to aluminum compounds in general: After swallowing: only slightly absorbable via the gastrointestinal tract. Serious disorders in man (from about 4000 mg aluminum up): phosphate metabolism, calcium metabolism.

The following applies to lithium compounds in general: when handled or used inappropriately, the absorption of large quantities is followed by CNS disorders, agitation, spasms, ataxia (impaired locomotor coordination) due to disturbed electrolyte balance.

### Indication of any immediate medical attention and special treatment needed

No information available.

---

## SECTION 5. Fire-fighting measures

### Extinguishing media

*Suitable extinguishing media*

Sand, Cement, Dry powder

*Unsuitable extinguishing media*

Water, Carbon dioxide (CO<sub>2</sub>), Foam

### Special hazards arising from the substance or mixture

Combustible material, Risk of dust explosion.

Development of hazardous combustion gases or vapors possible in the event of fire.

Caution! in contact with water product releases:

Hydrogen

### Advice for firefighters

*Special protective equipment for fire-fighters*

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

*Further information*

Prevent fire extinguishing water from contaminating surface water or the ground water system.

Cool closed containers exposed to fire with water spray.

---

## SECTION 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid substance contact. Avoid inhalation of dusts.

Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

### Environmental precautions

Do not let product enter drains. Explosive properties

### Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

---

## SECTION 7. Handling and storage

### Precautions for safe handling

---

# MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number 818878  
Product name Lithium aluminium hydride (tablets) for synthesis

Version 1.0

Observe label precautions.

Keep workplace dry. Do not allow product to come into contact with water.

## Conditions for safe storage, including any incompatibilities

Dry. Tightly closed. Keep away from heat and sources of ignition.

Store at +15°C to +25°C (+59°F to +77°F).

## SECTION 8. Exposure controls/personal protection

### Exposure limit(s)

#### Ingredients

Basis	Value	Threshold limits	Remarks
<i>aluminium lithium hydride 16853-85-3</i>			
ACGIH	Time Weighted Average (TWA):	1 mg/m <sup>3</sup>	Form of exposure: Respirable fraction.
NIOSH/GUIDE	Recommended exposure limit (REL):	2 mg/m <sup>3</sup>	Expressed as: as Al
Z1A	Time Weighted Average (TWA):	2 mg/m <sup>3</sup>	Expressed as: as Al

### Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

### Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

#### Hygiene measures

Immediately change contaminated clothing. Apply skin- protective barrier cream. Wash hands and face after working with substance.

#### Eye/face protection

Tightly fitting safety goggles

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### Other protective equipment:

Flame retardant antistatic protective clothing

#### Respiratory protection

required when dusts are generated.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## SECTION 9. Physical and chemical properties

Physical state solid

## MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Version 1.0

Product number	818878
Product name	Lithium aluminium hydride (tablets) for synthesis

---

Color	white
Odor	odorless
Odor Threshold	No information available.
pH	No information available.
	125 °C (decomposition)
Boiling point/boiling range	not applicable
Flash point	No information available.
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Vapor pressure	No information available.
Relative vapor density	No information available.
Relative density	0.917 g/cm <sup>3</sup> at 68 °F ( 20 °C)
Water solubility	at 68 °F ( 20 °C) (rigorous decomposition)
Partition coefficient: n-octanol/water	not applicable
Autoignition temperature	No information available.
Decomposition temperature	> 257 °F ( > 125 °C)
Viscosity, dynamic	No information available.
Explosive properties	No information available.
Bulk density	400 kg/m <sup>3</sup>

---

### SECTION 10. Stability and reactivity

#### Reactivity

Risk of dust explosion.

## MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

818878

Version 1.0

Product name

Lithium aluminium hydride (tablets) for synthesis

---

### Chemical stability

sensitive to moisture

### Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapors with:

Water, Oxygen, Alcohols, Acids

Risk of explosion with:

boron compounds, Ether, Dioxane, Organic Substances, Oxidizing agents, amides, hydrogen peroxide, Esters, acetonitrile, Peroxides

Exothermic reaction with:

Aldehydes, pyridine

### Conditions to avoid

Heat.

Exposure to moisture.

### Incompatible materials

no information available

### Hazardous decomposition products

no information available

---

## SECTION 11. Toxicological information

### Information on toxicological effects

#### *Likely route of exposure*

Eye contact, Skin contact, Ingestion

#### *Acute oral toxicity*

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

#### *Acute inhalation toxicity*

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages: damage of respiratory tract, Mucous membranes, Lungs

Corrosive to respiratory system

#### *Skin irritation*

Causes severe burns.

#### *Eye irritation*

Causes serious eye damage. Risk of corneal clouding. Risk of blindness!

#### *Specific target organ systemic toxicity - single exposure*

The substance or mixture is not classified as specific target organ toxicant, single exposure.

#### *Specific target organ systemic toxicity - repeated exposure*

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

#### *Aspiration hazard*

Regarding the available data the classification criteria are not fulfilled.

### Carcinogenicity

IARC

No ingredient of this product present at levels greater than or

---

## MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

818878

Version 1.0

Product name

Lithium aluminium hydride (tablets) for synthesis

---

	equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
ACGIH	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

### Further information

Quantitative data on the toxicity of this product are not available.

Further toxicological data:

Decomposition of the substance with tissue moisture.

Other information

The following applies to lithium compounds in general: when handled or used inappropriately, the absorption of large quantities is followed by CNS disorders, agitation, spasms, ataxia (impaired locomotor coordination) due to disturbed electrolyte balance.

The following applies to aluminum compounds in general: After swallowing: only slightly absorbable via the gastrointestinal tract. Serious disorders in man (from about 4000 mg aluminum up): phosphate metabolism, calcium metabolism.

Further data:

Handle in accordance with good industrial hygiene and safety practice.

---

## SECTION 12. Ecological information

### Ecotoxicity

No information available.

### Persistence and degradability

#### *Biodegradability*

The methods for determining the biological degradability are not applicable to inorganic substances.

### Bioaccumulative potential

*Partition coefficient: n-octanol/water*

not applicable

### Mobility in soil

No information available.

### Other adverse effects

*Additional ecological information*

Biological effects:

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information on ecology

# MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number 818878  
Product name Lithium aluminium hydride (tablets) for synthesis

Version 1.0

Discharge into the environment must be avoided.

## SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

## SECTION 14. Transport information

### Land transport (DOT)

UN number UN 1410  
Proper shipping name LITHIUM ALUMINIUM HYDRIDE  
Class 4.3  
Packing group I  
Environmentally hazardous --

### Air transport (IATA)

UN number UN 1410  
Proper shipping name LITHIUM ALUMINIUM HYDRIDE  
Class 4.3  
Packing group I  
Environmentally hazardous --  
Special precautions for user yes  
IATA ( Passenger) Not permitted for transport

### Sea transport (IMDG)

UN number UN 1410  
Proper shipping name LITHIUM ALUMINIUM HYDRIDE  
Class 4.3  
Packing group I  
Environmentally hazardous --  
Special precautions for user yes  
EmS F-G S-M

## SECTION 15. Regulatory information

### United States of America

#### OSHA Hazards

Water Reactive  
Corrosive to skin  
Corrosive by inhalation.

This information is based on 29 CFR 1910.1200 criteria prior to adoption of the GHS, and may deviate from the GHS information on the label and in section 2.



# MATERIAL SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

818878

Version 1.0

Product name

Lithium aluminium hydride (tablets) for synthesis

---

## SARA 311/312 Hazards

Reactivity Hazard

Acute Health Hazard

## SARA 313

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 302

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

## Massachusetts Right To Know

*Ingredients*

aluminium lithium hydride

## Pennsylvania Right To Know

*Ingredients*

aluminium lithium hydride

## New Jersey Right To Know

*Ingredients*

aluminium lithium hydride

## Notification status

TSCA:

On TSCA Inventory

DSL:

This product contains one or several components listed in the Canadian NDSL.

*Ingredients*

aluminium lithium hydride

---

## SECTION 16. Other information

### Training advice

Provide adequate information, instruction and training for operators.

### Full text of H-Statements referred to under sections 2 and 3.

H260

In contact with water releases flammable gases which may ignite spontaneously.

H314

Causes severe skin burns and eye damage.

### Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at [www.wikipedia.org](http://www.wikipedia.org).

---

MATERIAL SAFETY DATA SHEET  
according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number	818878
Product name	Lithium aluminium hydride (tablets) for synthesis

---

Version 1.0

Date of issue:02/04/2013

---

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

***All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.***