

Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Dimethyl Sulfoxide

MSDS Number : 000000011715

Product Use Description : Solvent

Manufactured for : VWR International LLC

Radnor Corporate Center

Building One Suite 200

100 Matsonford Road Radnor PA 19087

For more information call : (Monday-Friday, 8.00am-5:00pm)

1-800-932-5000

In case of emergency call : (24 hours/day, 7 days/week)

1-800-424-9300(USA Only)

For Transportation Emergencies:

1-800-424-9300 (CHEMTREC - Domestic) 1-613-996-6666 (CANUTEC - Canada)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid

Color : colourless

Odor : garlic/onion



Dimethyl Sulfoxide

BDH1115

Print Date 05/08/2015 Version 1.5 Revision Date 03/25/2015

Classification of the substance or mixture

Classification of the substance : Flammable liquids, Category 4

or mixture

GHS Label elements, including precautionary statements

Signal word : Warning

Hazard statements : Combustible liquid

Precautionary statements : Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

Wear protective gloves/ eye protection/ face protection.

Response:

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with local, state &

federal regulations.

Hazards not otherwise

classified

: May cause eye and skin irritation.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C2H6OS

Page 2 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

Chemical nature : Substance

Chemical Name	CAS-No.	Concentration
Dimethyl sulfoxide	67-68-5	100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician if

irritation develops or persists.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician if irritation develops or

persists.

Ingestion : Do not induce vomiting without medical advice. Never give

anything by mouth to an unconscious person. Call a physician.

Notes to physician

Treatment : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Dry chemical

Foam

Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing

media

: Do not use a solid water stream as it may scatter and spread

fire.

Page 3 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

Specific hazards during

firefighting

: Combustible.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as: Formaldehyde Methyl mercaptan Sulfur dioxide

Carbon dioxide (CO2) Carbon monoxide

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods for cleaning up : Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, soak up with non-combustible absorbent

Page 4 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Wear personal protective equipment.

Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke. Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Advice on protection against :

fire and explosion

Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and sources

of ignition.

No sparking tools should be used.

No smoking.

Storage

Requirements for storage areas and containers

Store in area designed for storage of flammable liquids. Protect

from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or expose

containers to heat or sources of ignition.

Page 5 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : Use with local exhaust ventilation.

Prevent vapour buildup by providing adequate ventilation during

and after use.

Eye protection : Do not wear contact lenses.

Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Protective suit

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

For rescue and maintenance work in storage tanks use

self-contained breathing apparatus.

Use NIOSH approved respiratory protection.

Hygiene measures : When using, do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the

product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Page 6 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

Exposure Guidelines

Exposure duidennes							
Components	CAS-No.	Value	Control parameters	Upda te	Basis		
Dimethyl sulfoxide	67-68-5	TWA: time weighted average	(250 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Color : colourless

Odor : garlic/onion

pH : Note: Not applicable

Melting point/freezing point : 18.5 ℃

Boiling point/boiling range : 189 ℃

Flash point : 190 °F (88 °C)

Method: closed cup

Lower explosion limit : 2 %(V)

Upper explosion limit : 42 %(V)

Vapor pressure : 0.61 hPa

at 20 °C(68 °F)

Page 7 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

Vapor density : 2.7

Density : 1.1004 g/cm3 at 20 ℃

1.0954 g/cm3 at 25 °C

Water solubility : Note: soluble

Ignition temperature : 215 ℃

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

Incompatible materials to

avoid

: Hazardous polymerisation does not occur.

: Oxidizing agents Strong acids Reducing agents

Alkali metals Boron compounds

Plastics

Metal salts of oxoacids

Acyl halides
Aryl halides
Non metal halides
Methyl bromide
Non-metallic chlorides
Active halogen compounds

Hazardous decomposition

products

: Hazardous decomposition products due to incomplete

combustion

Page 8 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

Formaldehyde Sulphur dioxide Methyl mercaptan Carbon dioxide (CO2) Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50: 14,500 mg/kg

Species: Rat

Acute inhalation toxicity : LC0: > 5,330 mg/m3

Exposure time: 4 h Species: Rat Note: No deaths

Acute dermal toxicity : LD50: 40,000 mg/kg

Species: Rat

Skin irritation : Species: Rabbit

Result: slight irritation

Method: OECD Test Guideline 404

Exposure time: 4 h

Eye irritation : Species: Rabbit

Result: slight irritation

Method: OECD Test Guideline 405

Sensitisation : Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Repeated dose toxicity : Species: Rat, male

Page 9 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Print Date 05/08/2015 Revision Date 03/25/2015

> Application Route: Inhalation Exposure time: 2 Weeks

No observed adverse effect level: 1100 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : flow-through test

> LC50: 34,000 mg/l Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Note: static test

: static test

LC50: 40,000 mg/l Exposure time: 96 h

Species: Lepomis macrochirus (Bluegill sunfish)

Note: static test

Toxicity to daphnia and other : static test

aquatic invertebrates

LC50: 24,600 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

Further information on ecology

SECTION 13. DISPOSAL CONSIDERATIONS

: Dispose of contents/ container in accordance with local, state, Disposal methods

and federal regulations.



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : NA 1993

> Proper shipping name : Combustible liquid, n.o.s.

(Dimethyl sulfoxide)

Class CBL Packing group Ш Hazard Labels NONE Required only for US-DOT Bulk Shipments

TDG Not dangerous goods

IATA Not dangerous goods

IMDG Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian **Environmental Protection** Act (CEPA). Domestic Substances List (DSL)

: All components of this product are on the Canadian DSL.

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous

: On the inventory, or in compliance with the inventory

Page 11 / 13



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

and Nuclear Waste Control

Act

China. Inventory of Existing

Chemical Substances

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

. Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

WHMIS Classification : B3: Combustible Liquid

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required

by the CPR.



Dimethyl Sulfoxide

BDH1115

Version 1.5 Revision Date 03/25/2015 Print Date 05/08/2015

SECTION 16. OTHER INFORMATION

Health hazard : 1 2
Flammability : 2 2
Physical Hazard : 0
Instability : 0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 06/19/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group