Safety Data Sheet



Orange G-6

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

1.1 Product Identifier

Trade Name : Orange G-6

Product Number : 3801660; 3801661; 3801662

SDS Date : September 2, 2015

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Product Use : Cytologic stain.
Uses Advised Against : All other uses.

1.3 Details of the Supplier of the Substance or Mixture

Manufacturer/Preparer : Leica Biosystems Richmond, Inc

5205 Route 12 Richmond, IL 60071 800-225-3035

LBSNA-LBS-QA@LEICABIOSYSTEMS.COM

1.4 Emergency Telephone Number

Emergency Spill : 1-800-424-9300 (ChemTrec)

+1 703-527-3887 International calls (call collect)

13 11 26 (Australia 24 Hr Poisons Information Centre)

Other Information : 1-800-225-3035

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

CLP/GHS Classification (1272/2008)

Physical:	Health:	Environmental:
Flammable Liquid – Category 2	Specific Target Organ Toxicity –	Not hazardous
	Single Exposure – Category 1	

2.2 Label Elements

Hazard Pictograms :



Signal Word : DANGER!

Hazard Statements : H225 Highly flammable liquid and vapour.

		H370	Causes damage to nervous system and eyes.
Precautionary Statements	:	P210	Keep away from heat/sparks/open flames/hot surfacesNo smoking.
		P233	Keep container tightly closed.
		P240	Ground/bond container and receiving equipment.
		P241	Use explosion-proof electrical/ventilating/liquid equipment.
		P242	Use only non-sparking tools.
		P243	Take precautionary measures against static discharge.
		P260	Do not breathe mist/vapours/spray.
		P264	Wash thoroughly after handling.
		P270	Do not eat, drink, or smoke when using this product.
		P280	Wear protective gloves/protective clothing/eye protection/face
			protection.
		P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
			Rinse skin with water/shower.
		P308+P313	IF exposed or concerned: Get medical advice/attention.
		P370+378	In case of fire: Use dry chemical, alcohol-resistant foam, carbon dioxide
			(CO ₂), or water spray for extinction.
		P403+P235	Store in a well-ventilated place. Keep cool.
		P405	Store locked up.
		P501	Dispose of contents/container in accordance with all local and national regulations.

2.3 Other Hazards

Other hazards which do not result in classifications : None known.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number / EINECS Number / REACH Reg. Number	% (w/w)	CLP/GHS Classification (1272/2008)	
Ethanol	64-17-5 200-578-6	<80	Flammable Liquid – Category 2 (H225)	
Methanol	67-56-1 200-659-6	<5	Flammable Liquid — Category 2 (H225) Acute Toxicity — Category 3 (H301, H311, H331) Specific Target Organ Toxicity — Single Exposure — Category 1 (H370)	
Isopropanol	67-63-0 <5 Flammable Liquid – Category 2 (H225) 200-661-7 Eye Irritation – Category 2A (H319)		Eye Irritation – Category 2A (H319) Specific Target Organ Toxicity (Single Exposure) – Category 1	

See Section 16 for full text of GHS and EU Classifications.

SECTION 4: FIRST AID MEASURES

4.1 Description of First Aid Measures

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least

20 minutes, occasionally lifting upper and lower eyelids. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 20 minutes while

removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly

after handling. Get medical attention immediately.

Inhalation: Call medical doctor or poison control center immediately. Move exposed person to fresh air. If not

breathing, if breathing is irregular, or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing, such as a collar, tie, belt, or waistband. Get

medical attention immediately.

Ingestion : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person. Get medical attention

immediately.

See Section 11 for more detailed information on health effects.

4.2 Most important symptoms and effects, both acute and delayed

Eye contact : May cause eye irritation.
Skin contact : May cause skin irritation.

Inhalation: Inhalation of vapors may cause nose, throat, or upper respiratory tract irritation and nervous

system effects, including dizziness, drowsiness, nausea, vomiting, visual disturbances, and

unconsciousness.

Ingestion: Harmful or fatal if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Immediate medical treatment is required for ingestion.

Specific treatments : No specific treatment.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing Media

Suitable extinguishing media : Use dry chemical, alcohol foam, carbon dioxide (CO₂), or water spray.

Unsuitable extinguishing media: None known.

5.2 Special hazards arising from the substance or mixture

Unusual fire and explosion hazards : Highly flammable liquid and vapor. Vapors are heavier than air and will travel along

surfaces to remove ignition sources and flash back. Vapors will collect in low areas.

Vapors may be ignited by static sparks. Flames may be invisible in daylight.

Combustion products : Oxides of carbon; smoke.

5.3 Advice for fire-fighters

Special protective equipment

for fire-fighters

Self-contained breathing apparatus and protective clothing should be worn in fighting

large fires involving chemicals.

Special protective action for

fire-fighters

Determine the need to evacuate or isolate the area according to your local emergency

plan. Use water spray to keep fire exposed containers cool.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment, and emergency procedures

For emergency responders : Wear appropriate protective equipment. Eliminate all ignition sources and ventilate the area with explosion-proof equipment. Do not touch or walk

through spilled material.

6.2 Environmental precautions

Environmental precautions: Prevent entry in storm sewers and waterways. Report spill as required by

local and federal regulations.

6.3 Methods and materials for containment and cleaning up

For small or large spill : Stop still at the source if it is safe to do so. Absorb with an inert material.

Use non-sparking tools and equipment. Collect into a suitable container for

disposal.

6.4 Reference to other sections

Refer to Section 8 for personal protective equipment, and Section 13 for disposal information.

SECTION 7: HANDLING and STORAGE

7.1 Precautions for safe handling

Protective measures: Prevent eye and skin contact. Do not breathe vapors or mists. Use only with adequate

ventilation. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse. Keep product away from heat, sparks, and all other sources of

ignition. Electrically bond and ground transfer equipment.

7.2 Conditions for safe storage, including any incompatibilities

Use appropriately rated electrical equipment in areas where this material is handled and stored. Keep containers closed when not in use. Store away from oxidizers. Empty containers retain product residues. Do not cut, weld, braze, etc. on or near empty containers. Follow all SDS precautions in handling empty containers.

7.3 Specific end use(s)

Industrial uses:None identified.Professional uses:Cytologic stain.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Chemical Name US OEL		EU IOEL	UK OEL	Germany OEL
Ethanol	1000 ppm TWA	None established	1000 nnm TW/	500 ppm TWA
Ethanor	1000 ppm STEL	None established	1000 ppm TWA	1000 ppm STEL
Methanol	200 ppm TWA	200 ppm TWA skin	200 ppm TWA	200 ppm TWA
ivietilalioi	250 ppm STEL skin	200 ppili TWA skili	250 ppm STEL	800 ppm STEL
Isopropanol	400 ppm OSHA PEL		400 ppm TM/A	
	200 ppm ACGIH TLV	None established	400 ppm TWA 500 ppm STEL	200 ppm TWA
	400 ppm STEL		200 hhiii 21EF	

Refer to local or national authority for exposure limits not listed above.

Chemical Name	Biological Limit Value
Methanol Methanol in urine 15 mg/L, end of shift (ACGIH)	
Isopropanol Acetone in urine 40 mg/L, end of shift at end of workweek (ACGIH)	

8.2 Exposure controls

Recommended monitoring

procedure

Ethanol: Collection on charcoal tubes with analysis by gas

chromatography.

Methanol: Collection on silica gel tubes with analysis by gas

chromatography.

Appropriate engineering controls : Use with adequate local exhaust ventilation to maintain exposure levels below the

occupational exposure limits.

Personal protective measures

Eye/face protection

: Wear safety glasses or chemical goggles.

Skin protection : Impervious clothing as needed to avoid skin contact.

Hands : Impervious gloves recommended (butyl rubber).

Respiratory protection: None needed with adequate ventilation. If the occupational exposure limit is

exceeded, use an approved respirator with organic vapor/formaldehyde cartridges. (In the United States, refer to 29 CFR 1910.1048 for cartridge change schedule requirements). Selection of respiratory protection depends on the contaminant type, form, and concentration. Select in accordance with OSHA 1910.134 or other applicable regulations and good industrial hygiene practice.

Other protection : Suitable washing facilities should be available.

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance : Light orange liquid

Odor Fragrant **Odor threshold** Not applicable рΗ Not available Melting/freezing point Not available **Boiling point** Not available Flash point 55°F (12°C) Lower flammability limit Not available Upper flammability limit Not available **Evaporation rate** Not available Vapor density (air = 1) Not available Vapor pressure Not available

Specific gravity ($H_2O = 1$) : 0.79 Relative density : 0.79

Solubility: Soluble in waterOctanol/water partition coefficient: Not availableAutoignition temperature: Not availableDecomposition temperature: Not availableViscosity: Not available

Explosive properties : Vapors may be explosive in confined areas

Oxidizing properties : None

Molecular formula: Not availableMolecular weight: Not available

9.2 Other information

No additional information available

SECTION 10: STABILITY and REACTIVITY

10.1 Reactivity : This material is not reactive under normal conditions.

10.2 Chemical stability : Normally stable.

10.3 Possibility of hazardous reactions : Reaction with strong oxidizers will generate heat and cause fire.

10.4 Conditions to avoid : Avoid heat, sparks, flames, and all other sources of ignition.

10.5 Incompatible materials : Oxidizing agents, strong acids, and bases.

10.6 Hazardous decomposition products : Thermal breakdown of this product during fire or very high heat conditions

may evolve the following decomposition products: oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Potential health effects:

Eye contact: Causes irritation with redness, tearing, and swelling.

Skin contact: Causes irritation and dryness. Repeated exposure may cause dermatitis. May be harmful if

absorbed through skin.

Inhalation : May cause respiratory tract irritation and central nervous system effects, such as dizziness,

drowsiness, nausea, vomiting, visual disturbances, and unconsciousness.

Ingestion: Swallowing may cause irritation of the mouth, throat, and stomach. This may include

abdominal pain, nausea, vomiting, and diarrhea. May cause central nervous system effects, including dizziness, drowsiness, nausea, vomiting, visual disturbances, and unconsciousness.

May cause permanent blindness.

Acute toxicity:

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	LD50 Oral	Rat	7,060 mg/kg	-
	LC50 Inhalation	Rat	20,000 ppm	10 hr
Methanol	LD50 Oral	Rat	5,628 mg/kg	-
	LC50 Inhalation	Rat	64,000 ppm	4 hr
	LD50 Dermal	Rabbit	15,800 mg/kg	-
Isopropanol	LD50 Oral	Rat	5,045 mg/kg	-
	LD50 Dermal	Rabbit	12,800 mg/kg	-

Skin corrosion/irritation No data available for mixture. Eve damage/irritation No data available for mixture. No data available for mixture. **Respiratory irritation** Respiratory sensitization No data available for mixture. Skin sensitization No data available for mixture. Germ cell mutagenicity No data available for mixture. Carcinogenicity No data available for mixture. **Reproductive Toxicity** No data available for mixture.

Specific Target Organ Toxicity:

Single exposure : Methanol has been found to cause visual and nervous system damage in studies with humans

and animals.

Repeat exposure : Ethanol, when consumed as a beverage, has been found to cause damage to the liver,

nervous system, and reproductive system.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Ethanol	nol LC50 13,000 mg/L		96 hours
	LC50 9,268 – 14,221 mg/L	Daphnia magna	48 hours
	EC50 9,310 mg/L	Green algae	48 hours
Methanol	LC50 29,400 mg/L	Fathead minnow	96 hours
	EC50 >10,000 mg/L	Daphnia magna	24 hours
Isopropanol	LC50 11,130 mg/L	Fathead minnow	48 hours
	LC50 1,400 mg/L	Brown shrimp	48 hours

12.2 Persistence and degradability : No data available.

12.3 Bioaccumulative potential : No data available.

12.4 Mobility in soil : No data available.

12.5 Results of PVT and vPvB assessment : No data available.

12.6 Other adverse effects : No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORTATION INFORMATION

	14.1	14.2	14.3	14.4	14.5
	UN Number	UN proper shipping name	Hazard class(es)	Packing group	Environmental hazards

US DOT	UN1987	Alcohols, N.O.S., (Contains: Ethanol, Methanol)	3	II	No
Canada TDG	UN1987	Alcohols, N.O.S., (Contains: Ethanol, Methanol)	3	II	No
EU ADR/RID	UN1987	Alcohols, N.O.S., (Contains: Ethanol, Methanol)	3	II	No
IMDG	UN1987			II	No
IATA	UN1987	Alcohols, N.O.S., (Contains: Ethanol, Methanol)	3	II	No

14.6 Special precautions for user : None.

14.7 Transport in bulk according to Annex

III MARPOL 73/78 and the IBC Code

Not determined

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US Regulations

OSHA hazard classification : Flammable; irritant; target organ effects

TSCA Inventory : All of the components are listed on the TSCA Inventory.

SARA 302 : This product does not contain any chemicals regulated under SARA 302.

SARA 311 Hazard Classification : Acute health hazard; chronic health hazard; fire hazard

SARA 313 : This product contains the following chemicals that are regulated under SARA

Title III, Section 313:

	Product name	CAS number	%
Form R – Reporting requirements	Methanol	67-56-1	<5
Supplier notifications	Methanol	67-56-1	<5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to the copies of the SDS subsequently redistributed.

CERCLA Section 103 : The RQ for the product, based on the RQ for Ethanol (5% maximum) of 5,000

lbs is 100,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state, and local

regulations.

California Prop 65 : This product contains the following chemical(s) which are known to the state of

California to cause cancer, reproductive toxicity, or birth defects:

Product name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Methanol	No	Yes	No	No

SECTION 16: OTHER INFORMATION

Revision history : Updated formatting

CLP/GHS Classification and H Phrases for Reference (See Section 3)

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to nervous system and eyes.

NFPA Rating Health: 3 Fire: 3 Instability: 0
HMIS Rating Health: 3 Fire: 3 Physical Hazard: 0

Notice to reader:

This Safety Data Sheet (SDS) has been prepared in accordance with the Classification, Labelling, and Packaging (CLP) regulation in the EU and the Globally Harmonized System (GHS) (29CFR 1910.1200) in the US. It complies with the requirements of the Canadian Controlled Products Regulations. To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.