

Page: 1/6

#### **HA Ultrogel**®

### Section 1. Chemical product and company identification

Common name : HA Ultrogel ®

**Synonym**: Agarose/hydroxyapatite beads suspended in ethanol aqueous solution.

Code : 24775

Material uses : Purification of biomolecules by chromatography.

Contact in France : Pall France

48 Avenue des Genottes F-95800 Cergy St Christophe

Tel: 33-1-3420-7800

Contact in US : Pall Corporation

2200 Northern Blvd East Hills, NY 11548 Tel: +1 516 484 5400

In case of emergency : CHEMTREC: 800-424-9300

#### Section 2. Hazards identification

Physical state : Liquid.

Odor : Ethanol
Color : White.

**Hazard status**: This material is classified as hazardous under OSHA regulations.

**Emergency overview** : WARNING!

CAUSES EYE IRRITATION.

CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS: BLOOD, REPRODUCTIVE SYSTEM, LIVER, RESPIRATORY TRACT, SKIN, CENTRAL

NERVOUS SYSTEM, EYE, LENS OR CORNEA.

FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY CAUSE SKIN IRRITATION.

Avoid contact with skin and clothing. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation.

Potential acute health effects

Eyes : Irritating to eyes.

**Skin**: Moderately irritating to the skin.

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Potential chronic health

effects

: Carcinogenic effects Classified A4 (Not classifiable for humans or animals.) by ACGIH

[Ethanol].

Mutagenic effects Not available. Teratogenic effects Not available.

Medical conditions aggravated by over-

aggravated by overexposure : Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to the substance can produce target organ damage.

See toxicological information (section 11)



HA Ultrogel® Page: 2/6

### Section 3. Composition, Information on Ingredients

**United States** 

% **Name CAS** number

Ethanol 64-17-5 16

See Sections 8, 11 and 14 for details.

#### Section 4. First aid measures

: Check for and remove any contact lenses. In case of contact with eyes, rinse **Eye contact** 

immediately with plenty of water. Get medical attention if symptoms occur.

Skin contact : Wash with soap and water. Get medical attention if symptoms occur.

Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical

attention if symptoms appear.

: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get Ingestion

medical attention if symptoms appear.

**Notes to physician** : No specific antidote. Medical staff must contact Poison Control Center.

# Section 5. Fire fighting measures

Flammability of the product : Flammable.

**Products of combustion** 

**Extinguishing media** 

Suitable

**Special protective** 

equipment for fire-fighters

These products are carbon oxides.

: Use dry chemical, carbon dioxide, water spray (fog) or foam.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

**Personal precautions** 

: Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment. Do not touch or walk through spilled material.

**Environmental precautions** 

: Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up

: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a nonsparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

## Section 7. Handling and storage

**Handling** 

: Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling.

**Storage** 

: Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Storage temperature: 2-30°C (36-86°F).

Pall Corporation provides the information contained herein in good faith and states that it represents the best information currently available. However, no warranties or representations are expressed or implied and Pall Corporation assumes no liabilities resulting from its use. Users should make their own investigations to determine the suitability of the information for their applications. In no way shall Pall Corporation be responsible for loses or damages resulting from the use or reliance upon this information.



HA Ultrogel ® Page: 3/6

## Section 8. Exposure controls, personal protection

**United States** 

**Product name Exposure limits** 

ACGIH TLV (United States, 1/2005).

TWA: 1880 mg/m<sup>3</sup> 8 hour(s). Form: All forms. TWA: 1000 ppm 8 hour(s). Form: All forms. NIOSH REL (United States, 12/2001).

TWA: 1900 mg/m<sup>3</sup> 10 hour(s). Form: All forms. TWA: 1000 ppm 10 hour(s). Form: All forms.

OSHA PEL (United States, 8/1997).

TWA: 1900 mg/m<sup>3</sup> 8 hour(s). Form: All forms. TWA: 1000 ppm 8 hour(s). Form: All forms.

**Engineering measures** 

Ethanol

: Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limit The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Personal protection** 

: Safety glasses. **Eyes** 

: Lab coat. Skin

Respiratory : A respirator is not needed under normal and intended conditions of product use.

Hands Natural rubber (latex)

: B







**HMIS Code/Personal** protective equipment

of a large spill

Hygiene measures

Personal protection in case: Safety glasses, goggles or face shield. Impervious gloves. Full suit. Boots. Wear NIOSHapproved self-contained breathing apparatus or equivalent and full protective gear.

> : Wash hands, forearms and face thoroughly after handling compounds and before eating. smoking and using the lavatory and at the end of the day. Follow good industrial hygiene practice.

## Section 9. Physical and chemical properties

**Physical state** : Liquid.

Flash point : Closed cup: 36°C (96.8°F).(Pensky-Martens.)

**Auto-ignition temperature** : The lowest known value is 398.85°C (749.9°F) (Ethanol).

Flammable limits : The greatest known range is Lower: 3.3% Upper: 19% (Ethanol)

Color : White. Odor : Ethanol

: 6 to 8 [Neutral.] pН

**Boiling/condensation point** : The lowest known value is 78.35°C (173°F) (Ethanol).

**Melting/freezing point** : May start to solidify at -113.89°C (-173°F) based on data for: Ethanol.

Relative density : 1 (Water = 1)

: 1.3 kPa (10 mm Hg) (at 20°C) Vapor pressure

Vapor density 1 (Air = 1)

**Odor threshold** : The lowest known value is 10 ppm (Ethanol)

Pall Corporation provides the information contained herein in good faith and states that it represents the best information currently available. However, no warranties or representations are expressed or implied and Pall Corporation assumes no liabilities resulting from its use. Users should make their own investigations to determine the suitability of the information for their applications. In no way shall Pall Corporation be responsible for loses or damages resulting from the use or reliance upon this information.



HA Ultrogel <sup>®</sup> Page: 4/6

Evaporation rate : >1

**Solubility** : Easily soluble in cold water, hot water.

## Section 10. Stability and reactivity

Stability and reactivity

: The product is stable.

Incompatibility with various

: Reactive with oxidizing materials, acids and alkalis.

substances

Hazardous polymerization : Will not occur.

**Conditions of reactivity** 

: Flammable in the presence of the following materials or conditions: open flames, sparks

and static discharge.

Slightly flammable in the presence of the following materials or conditions: heat.

### **Section 11. Toxicological information**

Toxicity data						
Product/ingredient name	Test	Result	Route	Species		
Ethanol	LD50	7060 mg/kg	Oral	Rat		
	LD50	6300 mg/kg	Oral	Rabbit		
	LD50	3450 mg/kg	Oral	Mouse		

**Acute Effects** 

**Eyes** : Irritating to eyes.

**Skin**: Moderately irritating to the skin.

Inhalation : No known significant effects or critical hazards.Ingestion : No known significant effects or critical hazards.

Potential chronic health

effects

: Carcinogenic effects Classified A4 (Not classifiable for humans or animals.) by ACGIH [Ethanol].

Mutagenic effects Not available.

Teratogenic effects: Not available.

**Target organs** 

: Contains material which causes damage to the following organs: blood, the reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or

cornea.

## **Section 12. Ecological information**

Ecotoxicity data						
Product/ingredient name	Species	Period	Result			
Ethanol	Daphnia magna (EC50)	48 hour(s)	2 mg/l			
	Daphnia magna (EC50)	48 hour(s)	9.3 mg/l			
	Daphnia magna (EC50)	48 hour(s)	>100 mg/l			
	Pimephales promelas (LC50)	96 hour(s)	>100 mg/l			
	Daphnia magna (LC50)	96 hour(s)	>100 mg/l			
	Oncorhynchus mykiss (LC50)	96 hour(s)	13000 mg/l			

**Environmental precautions** 

: No known significant effects or critical hazards.

**Products of degradation** 

: These products are carbon oxides .



HA Ultrogel® Page: 5/6

### Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional and local authority requirements.

### **Section 14. Transport information**

**Regulatory information** 

UN/ IMDG/IATA DOT: Not regulated.

Additional UN **IMDG** IATA DOT

information Not restricted, Special Provision A58

## **Section 15. Regulatory information**

**United States** 

**HCS Classification** : Flammable liquid

> Irritating material Target organ effects

**U.S. Federal regulations** 

: TSCA : All components listed.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Ethanol

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Ethanol:

Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

Clean Air Act (CAA) 112 regulated flammable substances: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

State regulations : Pennsylvania RTK: Ethanol: (generic environmental hazard)

Massachusetts RTK: Ethanol

New Jersey: Ethanol

California prop. 65: No products were found.

**International lists** : This product, (and its ingredients) is (are) listed on national inventories, or is (are)

exempted from being listed, Australia (AICS), in Europe (EINECS/ELINCS), in Korea

(TCCL), in Japan (METI), in the Philippines (RA6969).

### **Section 16. Other information**

Label requirements (U.S.A.) : CAUSES EYE IRRITATION.

CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS: BLOOD, REPRODUCTIVE SYSTEM, LIVER, RESPIRATORY TRACT, SKIN, CENTRAL

NERVOUS SYSTEM, EYE, LENS OR CORNEA.

FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY CAUSE SKIN IRRITATION.



HA Ultrogel <sup>®</sup> Page: 6/6

Hazardous Material Information System (U.S.A.)



#### **HAZARD RATINGS**

4- Extreme 3- Serious 2- Moderate 1- Slight

0- Minimal
See section 8 for more detailed information on personal protection.

National Fire Protection Association (U.S.A.)



References : ANSI Z400.1, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. -

29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous

Materials, UN#, Proper Shipping Names, PG.

Date of issue : 09/15/2006 Date of previous issue : 12/30/2005

Version : 2

® Indicates a trademark registered in the U.S.